



INTEGRATED CONTROLS, INC.

Web Based SCADA

Supervisory Control & Data Acquisition



WEB SCADA Remote PLC NEMA 4X
ALC WebDataLink (shown with HMI)



taking SCADA to the web

www.iciwebscada.com

Specification & Options:

Listing: UL cUL 508 / 698

NEMA Ratings Available : 1,12,3r,4,4x

Power: 24Vdc 0.400Ma base ; 120vac option; Solar, Wind

Note: Power consumption changes with added I.O.

Communications: Cell Data 940Mhz E-Net

I.O. Base: 8 Din

I.O. Options: Add D-in; D-out; A-in; A-out

I.O. Modules available in multiple combinations & configurations.

D-In: 24Vdc; 120Vac

D-Out: 24Vdc; 120Vac

A-in: 0-5Vdc; 0-10Vdc; 0-20ma; 4-20ma

Aout: 0-5 Vdc; 0-10Vdc; 0-20ma; 4-20ma

Iso Relay output for high current 0-10A output

Intrinsic Protection option for C1D1-D2 Area penetration

Software Functions:

Data Logging:

Memory: 2M / Log on event, time, or % Change

Data File Type: CSV w/ Header

Alarm Files

History Files

Data Rate: depends on cell network 19200 ~ 100k+

PLC Function:

Fully programmable

Comm Data Options: E-Net, Serial, Modbus, E-Net IP

Local HMI: Option, Graphic Touch